

SPECS	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Cubic Capacity*	Tare Weight	Maximum Payload*
STANDARD CONTAINERS								
20' Standard	19'4"	7'8"	7'10"	7'8"	7'6"	1,172 cft	4,916 lbs	47,900 lbs
	5.900 m	2.350 m	2.393 m	2.342 m	2.280 m	33.2 cbm	2,230 kg	21,770 kg
40' Standard	39'5"	7'8"	7'10"	7'8"	7'6"	2,390 cft	8,160 lbs	59,040 lbs
	12.036 m	2.350 m	2.392 m	2.340 m	2.280 m	67.7 cbm	3,700 kg	26,780 kg
40' H.C.(High Cube)	39'5"	7'8"	8'10"	7'8"	8'5"	2,694 cft	8,750 lbs	58,450 lbs
	12.036 m	2.350 m	2.697 m	2.338 m	2.585 m	76.3 cbm	3,970 kg	26,510 kg
OPEN TOP CONTAINERS								
20' Open Top	19'4"	7'7"	7'8"	7'6"	7'2"	1,136 cft	5,280 lbs	47,620 lbs
	5.894 m	2.311 m	2.354 m	2.286 m	2.184 m	32.2 cbm	2,400 kg	21,600 kg
40' Open Top	39'5"	7'8"	7'8"	7'8"	7'5"	2,350 cft	8,490 lbs	58,710 lbs
	12.038 m	2.350 m	2.345 m	2.341 m	2.274 m	65.5 cbm	3,850 kg	26,630 kg
REEFER CONTAINERS								
20' Reefer	17'8"	7'5"	7'5"	7'5"	7'3"	1,000 cft	7,040 lbs	45,760 lbs
	5.425 m	2.275 m	2.260 m	2.258 m	2.216 m	28.3 cbm	3,200 kg	20,800 kg
40' Reefer	37'8"	7'5"	7'2"	7'5"	7'0"	2,040 cft	10,780 lbs	56,276 lbs
	11.493 m	2.270 m	2.197 m	2.282 m	2.155 m	57.8 cbm	4,900 kg	25,580 kg
40' H.C.Reefer	37'11"	7'6"	8'2"	7'6"	8'0"	2,344 cft	9,900 lbs	57,561 lbs
	11.557 m	2.294 m	2.500 m	2.294 m	2.440 m	66.6 cbm	4,500 kg	25,980 kg
FLAT RACK CONTAINERS								
20' Flat Rack	18'5"	7'3"	7'4"	-	-	-	5,578 lbs	47,333 lbs
	5.620 m	2.200 m	2.233 m	-	-	-	2,530 kg	21,470 kg
40' Flat Rack	39'7"	6'10"	6'5"	-	-	-	12,081 lbs	85,800 lbs
	12.080 m	2.438 m	2.103 m	-	-	-	5,800 kg	39,000 k

All specifications are average measurements only.

This information is provided as a guide, to help you in determining the type of shipping container best suited to your needs. It is important to notice that some of these specs will vary from container to container, depending on the type of construction, the manufacturer etc. *Please note that the cubic capacity of these containers is shown as an absolute maximum. The shipping packages are mostly in different sizes and shapes; hence the actual capacity can be substantially below these figures.

* Maximum weight allowance on individual units and shipments may vary. U.S. DOT restricts maximum payload substantially lower than the payload shown above. Please contact Pro Cargo representative to check specific equipment payload.

Pro Cargo USA
Tel: 281 590 5500 / 888 778 8125 ♦ Fax: 281 590 1110
www.procargo.com